

Peran W

Product sheet

Product description

Peran W is a water based 1-component acrylic dispersion.

Uses

Peran W is used as a primer and flood layer in coloured flake systems (such as the Peran WA Accent Wall system).

Environment & Health

Peran W is a solvent free product, and practically odourless during application. Peran W is not classified as hazardous to health or environment. Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken.

For more information, please refer to the safety datasheets for the individual components.

Ratio of components

Peran W is a single component product.

Application temperature

The recommended substrate temperature is 15-25°C, but no less than 10°C. The temperature of the substrate should exceed the "dew point" by 3°C during application and hardening. Temperatures should not fall below 5°C in the 24 hrs after application.

Curing time (20°C)

Can be overcoated after 15 minutes.

Low relative humidity, max 70 %, and good ventilation are prerequisites to achieve the above drying time.

Colours

White.

Solids content

Approx. 75 %

Finish

Matt

Density

Approx. 1.4 kg/l.

Storage

12 months in an unopened pack at a temperature of 5-40°C. Protect from frost. Protect from weather and moisture/contaminant ingress.

Packaging

The product is supplied in the following packs:

Unit

12 kg (8.6 litres)

Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.