

# Isocrete Screedfast Flex (Green)

## Product sheet

### Product description

A specially formulated polymer modified cement giving a high early strength and very rapid drying screed. The sand and any required aggregate are supplied by the contractor.

### Uses

Fast track construction and refurbishment projects where the screed needs to be trafficked or overlaid quickly. Isocrete Screedfast may be laid bonded, unbonded or floating (for weight saving and thermal or sound insulation) and may be used with proprietary underfloor heating systems.

Isocrete Screedfast Flex (Green) can be used as a substrate for industrial resin screeds; especially Flowfresh HF, which can be applied directly to the abraded surface without primer.

### Environment & Health

Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken. For more information, please refer to the safety datasheet.

### Mixing and Application

See the relevant Application Instructions for full details of the application, equipment, mix designs and curing details.

Colour	Solids content	Density
Beige	Approx. 100 %	Approx. 2.5 kg/litre.

### Storage

6 months in unopened pack. Storage temperature between 6°C and 25°C.  
Protect from weather and moisture/contaminant ingress.

### Packaging

Isocrete Screedfast Flex (Green)      25 kg bag (40 bags supplied on one pallet)

*Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.*

When printed or saved externally this document is uncontrolled and may not be the latest version.