



THIN-CRETE COLOR PACK

INTEGRAL COLORANT FOR THIN-CRETE

COLORANTS / PIGMENT

THIN-CRETE COLOR PACK

MASTER FORMAT #: 00 00 00

DESCRIPTION

THIN-CRETE COLOR PACKS are pre-measured packages of integral colorants designed for use with THIN-CRETE GROUT. **THIN-CRETE COLOR PACKS** may also be used to color grouts and micro-toppings as well as SPRAY DECK GROUT when used as part of the TEXTURE CRETE SYSTEM.

PRIMARY APPLICATIONS

May be used with MICRO-CRETE, LEVEL TOP SP, and SPRAY-DECK GROUT (colours may vary).

FEATURES

- Light-fast, permanent colour
- Interior or exterior applications
- Pre-measured for easy mixing

TECHNICAL INFORMATION

THIN-CRETE COLOR PACKS are composed of light-fast, UV-stable, iron-oxide colorants and will not fade. Colorants meet or exceed the requirements of ASTM C979.

PACKAGING

THIN-CRETE COLOR PACKS weigh approximately 0.45 kg each and are available in 30 standard Increte colours. Pre-coloured THIN-CRETE GROUT or TEXTURE CRETE is available by special order. Special colours can be matched by request (minimum order requirements apply).

SHELF LIFE

4 Years in original, unopened container

COVERAGE

Each colour pack is pre-measured for use in one 22.5 kg bag of neutral THIN-CRETE grout.

DIRECTIONS FOR USE

MIXING:

Add contents of one full **THIN-CRETE COLOR PACK** to mix water. (See grout mixing instructions for water requirements). Mix until colorant is dispersed, then add grout while mixing. Apply as directed according to grout instructions.

PRECAUTIONS / LIMITATIONS

- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev: 09/09/16

DISCLAIMER: Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise. When printed or saved externally this document is uncontrolled and may not be the latest version.