

Compact White (STC Filler)

Product sheet

Product description

Free flowing filler, graded dolomite (calcium magnesium carbonate).
Also known as Peran STC Filler White or Compact Vit.

Uses

For mixing with Peran STC in Peran STB Compact and Peran ESD STB Compact systems to form the slurry coating.

Environment & Health

Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken. For more information, please refer to the safety datasheet.

Ratio of components

1:1 by weight with mixed Peran STC.

Mix the Peran STC A+B components with a slow speed drill and helical spinner and then add same weight of filler and mix.

Colour

White

Solids content

Approx. 100 %

Density

Approx. 2.85 kg/litre.

Storage

12 months in unopened pack.

Storage temperature between 5°C and 25°C.

Protect from weather and moisture/contaminant ingress.

Packaging

The product is delivered in the following packs:

Unit

12 kg (4.2 litres)

20 kg (7.0 litres)

Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.